

CHEM PRO 2280

PRINCIPAL USES

Chem Pro 2280 (Cleaner NP) is a specially formulated, low foaming blend of non-ionic surfactants, polymeric dispersants, and metal passivators designed to disperse airborne debris, oil and sludge in the precommissioning cleaning of closed loop circuits. Chem Pro 2280 will help to remove contaminants that reduce heat transfer and lead to under deposit corrosion. It enhances the performance of the ongoing treatment program by removing the contaminants which might prevent proper corrosion inhibition. This product does not contain any phosphate or phosphorous containing compounds.

GENERAL DESCRIPTION

APPEARANCE: Light yellow liquid.

ODOR: Odorless
PRODUCT pH: 13.0
DENSITY (lbs/gal): 8.4

FLASH POINT: Not Flammable

DOSAGE

Dosage requirements are dependent on the operating characteristics of your system, the water chemistry and the severity of fouling. Optimum results are typically achieved by feeding 1000 ppm (1 gal/1000 gal system volume) of product in the system's water. For moderate to heavily fouled systems an initial slug dosage of up to 10 gal/1000 gal system volume may be applied. Specific use instructions will be furnished by your Chem Pro Service Representative.

FEEDING

Chem Pro 2280 should be fed neat to the system by means of a bypass pot feeder.

HANDLING

Read the Safety Sheet (SDS) before using. Wear eye protection and rubber gloves when handling this product.

SHIPPING AND STORAGE

Chem Pro 2280 is supplied in 5 gallon pails, and 30 gallon and 55 gallon drums. Store in safe, dry area away from heat or freezing.