



## **CHEM PRO LAB INC**

WATER TREATMENT SPECIALISTS  
CHEMICAL ENGINEERS  
941 W 190TH ST, GARDENA, CA 90248  
310-532-8611 - [www.chemprolab.com](http://www.chemprolab.com)

## **PRODUCT DATA SHEET**

# **CHEM PRO 2700**

### **PRINCIPAL USES**

Chem Pro 2700 is used to reduce oxygen in boiler and reduces oxygen corrosion. Dissolved oxygen is responsible for major corrosion of feedwater systems, internal boiler and parts of condensate return piping. CPL 2700 will remove any residual dissolved oxygen.

### **GENERAL DESCRIPTION**

APPEARANCE:	Clear liquid
ODOR:	Odorless
PRODUCT pH:	8.3-8.7
DENSITY (lbs/gal):	9.8
FLASH POINT:	Not Flammable

### **DOSAGE**

Dependent on plant conditions, dose to control boiler water sulfite level at 30 - 60 ppm.

### **FEEDING**

By proportioning pump or by dosing to maintain 30 - 60 ppm sulfite in boiler water. This product should be fed to the storage section of the feedwater tank or deaerator.

### **HANDLING**

Read Safety Data Sheet (SDS) before using.  
Handle with care and protect containers from extreme temperatures.

### **SHIPPING AND STORAGE**

Chem Pro 2700 is supplied in 5 gallon pails, and 30 gallon and 55 gallon drums.  
Store in safe, dry area away from heat or freezing.