



CHEM PRO LAB INC

WATER TREATMENT SPECIALISTS
CHEMICAL ENGINEERS
941 W 190TH ST, GARDENA, CA 90248
310-532-8611 - www.chemprolab.com

PRODUCT DATA SHEET

CHEM PRO 2703

PRINCIPAL USES

Chem Pro 2703 is used to reduce oxygen in boiler and reduces oxygen corrosion. Dissolved oxygen is responsible for major corrosion of feedwater systems, internal boiler and parts of condensate return piping. CPL 2703 will remove any residual dissolved oxygen.

GENERAL DESCRIPTION

APPEARANCE:	Brown Powder.
ODOR:	Odorless
PRODUCT pH:	9-10 (1% solution)
FLASH POINT:	Not Flammable

DOSAGE

Dependent on plant conditions, dose to control boiler water sulfite level at 30 - 70 ppm.

FEEDING

By proportioning pump or by dosing to maintain 30 - 70 ppm sulfite in boiler water. This product should be fed to the storage section of the feedwater tank or deaerator below the water level.

HANDLING

Read Safety Data Sheet (SDS) before using.
Handle with care and protect containers from extreme temperatures.

SHIPPING AND STORAGE

Chem Pro 2703 is supplied in 25 pound and 50 pound pails.
Store in safe, dry area away from heat or freezing.