



CHEM PRO LAB INC

WATER TREATMENT SPECIALISTS
CHEMICAL ENGINEERS
941 W 190TH ST, GARDENA, CA 90248
310-532-8611 - www.chemprolab.com

PRODUCT DATA SHEET

CHEM PRO 2706

PRINCIPAL USES

Chem Pro 2706 is used to scavenge oxygen in boiler feedwater and reduces oxygen corrosion. Dissolved oxygen is responsible for major corrosion of feedwater systems, internal boiler and parts of condensate return piping. CPL 2706 will remove any residual dissolved oxygen.

GENERAL DESCRIPTION

APPEARANCE:	Yellow liquid.
ODOR:	Sulfur dioxide gas odor
PRODUCT pH:	3-4
DENSITY (lbs/gal):	11.1
FLASH POINT:	Not Flammable

DOSAGE

Dose to control boiler water sulfite level at 30 - 60 ppm, dependent on plant conditions.

FEEDING

By proportioning pump or by dosing to maintain 30 - 60 ppm sulfite in boiler water. This product should be fed to the storage section of the feedwater tank or deaerator.

HANDLING

Read Safety Data Sheet (SDS) before using.
Handle with care and protect containers from extreme temperatures.

SHIPPING AND STORAGE

Chem Pro 2706 is supplied in 5 gallon pails, and 30 gallon and 55 gallon drums.
Keep in a safe, well ventilated, cool, dry place.