

Section 1 - Identification

Product Name:	CPL 2860
Alternate Name:	Neutralizing Amine Morpholine/Cyclohexamine DEAE 20%
Recommended Use:	Boiler water treatment
Manufacturer:	Chem Pro Laboratory, Inc., 941 W 190th St, Gardena CA 90248, 310-532-8611
ChemTrec:	800-424-9300 (Transportation Spill Response 24 hours)

Section 2 - Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

DANGER



Suspected of damaging fertility or the unborn child

Flammable liquid and vapor

Causes severe skin burns and serious eye damage

Do not breathe dusts or mists.

Keep away from sparks and open flames. No smoking. Ground container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash contacted areas thoroughly after handling.

Wear eye and face protection, protective gloves and clothing, and protective gloves.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash skin with plenty of water. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IN CASE OF FIRE: Use carbon dioxide, dry chemical, or appropriate foam to extinguish.

Store locked up, in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with federal, state, and local regulations.

Section 3 - Composition/information on ingredients

Chemical Name	CAS Number	Percent
2-diethylaminoethanol (DEAE)	100-37-8	5-10%
cyclohexylamine	108-91-8	5-10%
morpholine	110-91-8	5-10%

Section 4 - First-aid measures

Emergency and First Aid Procedures:



CHEM PRO LAB INC WATER TREATMENT SPECIALISTS CHEMICAL ENGINEERS

SAFETY DATA SHEET CPL 2860

Inhalation	Remove to fresh air. Obtains medical assistance immediately.
Eye Contact	Flush eyes with water for 15 minutes. Get immediate medical attention.
Skin Contact	Wash contaminated areas of body with soap and water while removing contaminated clothing. Launder contaminated clothing before reuse. Get immediate medical attention.
Ingestion	Do not induce vomiting. Dilute with water or milk and get medical assistance immediately.
Symptoms of Overexposure:	
Inhalation	Inhalation of high concentrations of vapor may produce irritation of respiratory tract and lungs.
Contact with Skin or Eyes	Skin contact, with the liquid or vapors/mists may result in dermatitis and deep burns. Eye contact may result in burns and permanent injury.
Absorption Through Skin	Can be absorbed in toxic amounts.
Ingestion	Very toxic by ingestion.

Section 5 - Fire-fighting measures

Extinguishing Media	carbon dioxide, dry chemical, or appropriate foam
Fire Fighting Procedure	Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Water may be ineffective on flames but should be used to cool fire-exposed containers.
Unusual Fire/Explosion Hazard	Dangerous when exposed to heat or flames. Can react with oxidizing materials. Emits toxic gases when heated to decomposition.
Hazardous Combustion Product	s Oxides of nitrogen (NOx), oxides of carbon

Section 6 - Accidental release measures

Spill Response Procedure	Confine spilled material to prevent contamination in suitable containers for disposal in RCRA
	licensed facility. This material is RCRA hazardous due to it's properties.

Section 7 - Handling and storage

Handling Precautions	No special handling procedures are required.
Storage Conditions	Store in a cool dry place. Keep container tightly sealed in a dry and ventilated area. Do not store unopened containers in direct sunlight for extended periods.

Section 8 - Exposure controls/personal protection

Chemical Name	OSHA PEL	ACGIH TLV		
2-diethylaminoethanol (DEAE)	10 ppm TWA	2 ppm TWA		
cyclohexylamine	not listed	10 ppm TWA		
morpholine	20 ppm TWA	20 ppm TWA		
Ventilation	Local and mechanical (general) exhaust required.			
Respiratory Protection	If vapors or mists are generated, wear NIOSH/OSH	IA approved organic vapor/mist respirator.		
Protective Gloves	Clean neoprene rubber gloves.			
Eye Protection	Face shield or chemical splash goggles.			
Other Protective Equipment	Impervious clothing to protect exposed body areas.			
Work / Hygenic Practices	Safety showers and eyewash facilities required. Ex	plosion proof transfer pumps.		



Section 9 - Physical and chemical properties

Appearance	Colorless liquid.	Vapor Pressure @20°C	7 mm Hg @ 68 deg F
Odor	Characteristic amine odor	Vapor Density	3
Odor Threshold	Not Determined	Specific Gravity	1.00
рН	10-11	Solubility in Water	>10%
Melting Point, °F	23 deg F	Partition Coefficient	Not Determined
Boiling Point, °F	263 deg F	Auto Ignition Temp, °F	590 deg F
Flash Point, °F	95 deg F	Decomposition Temp, °F	Not Determined
Evaporation Rate	Not Determined	Viscosity	Not Determined
Flammability Limits	1.8-10.8%	Percent Volatile	100%

Section 10 - Stability and reactivity

Reactivity	in water: None.		
Stability	stable under normal conditions		
Conditions to Avoid	Avoid contact with mineral acids, copper, brass, open flames and oxidizing materials. Do not add or mix with nitrites.		
Incompatible Materials	Strong oxidizing agents. Strong acids.		
Hazardous Decomposition Prod	ucts Oxides of carbon and nitrogen may form in burning. Ammonia and hydrogen on reaction. irritating aldehydes and ketones may be formed.		
Hazardous Polymerization	Hazardous polymerization will not occur.		

Section 11 - Toxicological information

Routes of Entry	inhalation, skin or eye contact, ingestion		
Acute Exposure Symptoms	This material is	corrosive to body tissues.	
Chronic Exposure Effects	Possible damag	e to liver, lungs, kidneys, blood and blood forming organs.	
Medical Conditions Aggravated	By Exposure	No data is available which addresses medical conditions that are generally recognized as being aggravated by exposure to this product.	
Acute Toxicity:			

Chemical Name	CAS Number	Oral LD50	Dermal LD50	Inhalation LC50
2-diethylaminoethanol (DEAE)	100-37-8	1320 mg/kg	1113 mg/kg	5 mg/L
cyclohexylamine	108-91-8	303 mg/kg	631-1000 mg/kg	>39.2 mg/L
morpholine	110-91-8	1919 mg/kg	500 mg/kg	8 mg/L
Carcinogenicity:				

Ingredients are on the following lists of suspected or known carcinogens:

Chemical Name	CAS Number:	IARC	NTP	OSHA
2-diethylaminoethanol (DEAE)	100-37-8	No	No	No
cyclohexylamine	108-91-8	No	No	No
morpholine	110-91-8	No	No	No

Section 12 - Ecological information



Preparing Waste For Disposal	Incinerate or bury in RCRA licensed facility. Method must be approved by local, state and/or federal agency.	
Section 14 - Transport information		
DOT Shipping	UN1760, CORROSIVE LIQUID, N.O.S., 8, PG III, (MORPHOLINE)	
Section 15 - Regulatory information		
California Proposition 65 HMIS Ratings	This product does not contain chemicals listed by California proposition 65. Health: 3, Flammability: 1, Reactivity: 0	

Section 16 - Other information

Date Prepared	5/21/2015
Preparer	Michael Bortnik, Keith Johnson

The data in this Safety Data Sheet is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, Chem Pro Laboratory, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should have relative technical skills and satisfy himself that he has all current data relevant to his particular product and its applications.