

Section 1 - Identification

Product Name: CPL 3044

Alternate Name: Acidic Treatment With Organic Corrosion Inhibitor and Terpolymer

Recommended Use: Cooling tower water treatment

Manufacturer: Chem Pro Laboratory, Inc., 941 W 190th St, Gardena CA 90248, 310-532-8611

ChemTrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2 - Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

DANGER







Fatal if inhaled May cause cancer

Causes severe skin burns and serious eye damage

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not breathe dusts or mists.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Use only outdoors or in a well-ventilated area.

Wash contacted areas thoroughly after handling.

Wear eye and face protection, protective gloves and clothing, and respiratory protection.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash skin with plenty of water. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Store in a well-ventilated place. Keep container tightly closed, locked up.

Dispose of contents/container in accordance with federal, state, and local regulations.

Section 3 - Composition/information on ingredients

Chemical Name	CAS Number	Percent
sulfuric acid	7664-93-9	30-40%
aminotri(methylenephosphonic acid) (ATMP)	6419-19-8	1-5%
polyacrylate terpolymer	proprietary	1-5%
maleic acid copolymer	113221-69-5	1-5%
sodium polyacrylate	9003-04-7	1-5%
hydroxyphosphonoacetic acid (HPAA)	23783-26-8	<1%
2-phosphonobutane-1,2,4-tricarboxylic acid (PBTC)	37971-36-1	<1%

CPL 3044 Page 1/4

ACGIH TLV



Section 4 - First-aid measures

Emergency and First Aid Procedures:

Inhalation On over-exposure, remove to fresh air; get medical attention.

Eye Contact Flush with large quantities of water for at least 20 minutes, lifting upper and lower lids

occasionally. Contact a physician.

Skin Contact Flush thoroughly with water; wash with soap/water while removing all contaminated clothing

and shoes. Contact a physician.

Ingestion Do not induce vomiting; dilute by giving milk or water if conscious. Get medical attention

immediately.

Symptoms of Overexposure:

Inhalation Inhalation of mist can be injurious to lungs.

Contact with Skin or Eyes Skin and eye irritation.

Absorption Through Skin Skin irritation

Ingestion Burning. LD50 for sulfuric acid in rates 2.14 g/kg.

Section 5 - Fire-fighting measures

Extinguishing Media dry chemical

Fire Fighting Procedure H2SO3 can be released at high temperatures. Use respirator approved by NIOSH.

Unusual Fire/Explosion Hazard Reacts with most metals to form hydrogen gas which can form explosive mixture with air.

Hazardous Combustion Products Substance is noncombustible

Section 6 - Accidental release measures

Spill Response Procedure Flush with plenty of water and neutralize acid with soda ash, lime or bicarbonate of soda. Note:

Neutralization will release CO2 gas requiring adequate ventilation.

Section 7 - Handling and storage

Chemical Name

Handling Precautions Avoid all handling and storage procedures that may result in spills, leaks or punctures. Handle

and store in areas with unlimited water supply.

Storage Conditions Store in a cool dry place. Keep container tightly sealed in a dry and ventilated area. Do not

store unopened containers in direct sunlight for extended periods.

OSHA PEL

Section 8 - Exposure controls/personal protection

sulfuric acid 1 mg/m3 TWA 0.2 mg/m3 TWA aminotri(methylenephosphonic acid) (ATMP) 1 mg/m3 TWA, 3 mg/m3 STEL 1 mg/m3 TWA, 3 mg/m3 STEL 1 mg/m3 TWA, 3 mg/m3 STEL

polyacrylate terpolymer not listed not listed maleic acid copolymer not listed not listed sodium polyacrylate not listed not listed not listed

hydroxyphosphonoacetic acid (HPAA) 1 mg/m3 TWA, 3 mg/m3 STEL 1 mg/m3 TWA, 3 mg/m3 STEL

2-phosphonobutane-1,2,4-tricarboxylic acid (PBTC) not listed not listed

Ventilation Mechanical (general) exhaust required.

CPL 3044 Page 2/4



Respiratory Protection The use of respiratory protection depends on vapor concentration above the time-weighted

TLV; use NIOSH approved cartridge respirator or gas mask.

Protective Gloves Rubber or impermeable gloves.

Eve Protection Safety glasses, chemical goggles and or face shield.

Other Protective Equipment Impermeable aprons are advised. The availability of eye washes and safety showers in work

area is recommended.

Work / Hygenic Practices Handle in accordance with good industrial hygiene and safety practices.

Section 9 - Physical and chemical properties

Appearance Clear brown liquid Vapor Pressure @20°C 10mm 18 Deg F

Odor Odorless **Vapor Density** >1 **Odor Threshold** Not Determined 1.2 **Specific Gravity** На <1.0 Solubility in Water Complete Melting Point, °F 30 to 35 Deg F **Partition Coefficient** Not Determined **Boiling Point, °F** 200 Deg F Auto Ignition Temp, °F Non Flammable Flash Point, °F Decomposition Temp, °F Not Determined Not Flammable **Evaporation Rate** <1 Viscosity Not Determined

Flammability Limits N/A Percent Volatile N/A

Section 10 - Stability and reactivity

Reactivity in water: N/A

Stability stable under normal conditions

Conditions to Avoid Temperatures above 150 Deg F, Base (alkali), nitrites, chlorates and metal powders. Contact

with organic substances and metals.

Incompatible Materials Strong alkali

Hazardous Decomposition Products Sulfur trioxide gas (SO3) at high temperatures.

Hazardous Polymerization Hazardous polymerization will not occur.

Section 11 - Toxicological information

Routes of Entry inhalation, skin or eye contact, ingestion

Acute Exposure Symptoms Respiratory irritation and inflammation.

Chronic Exposure Effects Lung damage. Dental erosion. Causes severe burns.

Medical Conditions Aggravated By Exposure N/A

Acute Toxicity:

Chemical Name	CAS Number	Oral LD50	Dermal LD50	Inhalation LC50
sulfuric acid	7664-93-9	2140 mg/kg	no data	0.320 mg/L
aminotri(methylenephosphonic acid) (ATMP)	6419-19-8	no data	no data	no data
polyacrylate terpolymer	proprietary	no data	no data	no data
maleic acid copolymer	113221-69-5	3870 mg/kg	no data	no data
sodium polyacrylate	9003-04-7	>5000 mg/kg	>2000 mg/kg	no data
hydroxyphosphonoacetic acid (HPAA)	23783-26-8	2750	no data	no data
2-phosphonobutane-1,2,4-tricarboxylic acid (PBTC)	37971-36-1	>2000 mg/kg	>2000 mg/kg	no data

CPL 3044 Page 3/4



Carcinogenicity:

Ingredients are on the following lists of suspected or known carcinogens:

Chemical Name	CAS Number:	IARC	NTP	OSHA
sulfuric acid	7664-93-9	Yes	Yes	Yes
aminotri(methylenephosphonic acid) (ATMP)	6419-19-8	No	No	No
polyacrylate terpolymer	proprietary	No	No	No
maleic acid copolymer	113221-69-5	No	No	No
sodium polyacrylate	9003-04-7	No	No	No
hydroxyphosphonoacetic acid (HPAA)	23783-26-8	No	No	No
2-phosphonobutane-1,2,4-tricarboxylic acid (PBTC)	37971-36-1	No	No	No

Section 12 - Ecological information

Overview: No data

Section 13 - Disposal considerations

Preparing Waste For Disposal Neutralize acid with alkali and flush to sewer with plenty of water if permitted by local and state

regulations.

Section 14 - Transport information

DOT Shipping UN2796, SULFURIC ACID, SOLUTION, 8, PG II

Section 15 - Regulatory information

California Proposition 65 This product contains chemicals listed by California proposition 65.

HMIS Ratings Health: 3, Flammability: 0, Reactivity: 0

Section 16 - Other information

Date Prepared 5/22/2015

Preparer Michael Bortnik, Keith Johnson

The data in this Safety Data Sheet is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, Chem Pro Laboratory, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should have relative technical skills and satisfy himself that he has all current data relevant to his particular product and its applications.

CPL 3044 Page 4/4