



CHEM PRO LAB INC
WATER TREATMENT SPECIALISTS
CHEMICAL ENGINEERS
941 W 190TH ST, GARDENA, CA 90248
310-532-8611 - www.chemprolab.com

PRODUCT DATA SHEET

CHEM PRO 3755

PRINCIPAL USES

Chem Pro 3755 Antifoam is used to control foaming and carryover in all types of boilers. Can improve steam and reduces steam line deposits. Permits higher TDS in boiler and reduces flashing during load changes. Chem Pro 3755 Antifoam is a nonpolluting type. Meets all requirements of municipal, state and federal agencies of non-pollution of sanitary sewers and storm drains.

GENERAL DESCRIPTION

APPEARANCE:	White liquid
ODOR:	Slight ammoniacal odor
PRODUCT pH:	N/A
DENSITY (lbs/gal):	8.2
FLASH POINT:	Not Flammable

DOSAGE

Proper Chem Pro 3755 treatment levels depend on many factors specific to a given system. The product should be used in accordance with Chem Pro Laboratory, Inc. recommendations and procedures for a particular system.

FEEDING

The product should be used in accordance with Chem Pro Laboratory, Inc. recommendations and procedures for a particular system.

HANDLING

Read Safety Data Sheets (SDS) before using.

SHIPPING AND STORAGE

Chem Pro 3755 is supplied in boxes of four 1 gallon containers or 5 gallon pails. Store in safe, dry area away from heat or freezing.