



CHEM PRO LAB INC

WATER TREATMENT SPECIALISTS
CHEMICAL ENGINEERS
941 W 190TH ST, GARDENA, CA 90248
310-532-8611 - www.chemprolab.com

PRODUCT DATA SHEET

CHEM PRO 3810

PRINCIPAL USES

Chem Pro 3810 is a liquid alkaline organic, with molybdate, blended treatment for industrial closed and thermal storage systems. The recirculating water pH after the addition of the inhibitor will normally range 8.5 to 10.5. The inhibitor can be used in systems with city or deionized water. When water solutions of glycol are used, a special borate buffer additive should be added to the system. This product provides maximum corrosion protection by establishing a protective passivation film on both ferrous and copper alloy metals with typical corrosion rates less than 0.5 milliinches per year for carbon steel and less than 0.1 milliinches per year for copper alloys. In addition, Chem Pro 3810 does not contain components which will ordinarily feed bacterial growths or rapidly deplete under adverse conditions. This high performance corrosion inhibitor is currently being patented.

GENERAL DESCRIPTION

APPEARANCE:	Clear light brown liquid.
ODOR:	Odorless
PRODUCT pH:	11.8
DENSITY (lbs/gal):	9.8
FLASH POINT:	Not Flammable

DOSAGE

The product should be used in accordance with control procedures recommended by Chem Pro Laboratory, Inc. for a specific application. Initial dosage is generally 1 gallon of Chem Pro 3810 per 1000 gallons of system water.

FEEDING

The product is usually slug fed directly to the system.

HANDLING

Read Safety Data Sheets (SDS) before using. This material is an alkaline liquid. Wear rubber gloves and splash-proof goggles. In case of contact with skin, wash promptly with plenty of water. If contact with eyes, flush immediately with plenty of water for at least 15 minutes. In case of eye contact or ingestion, contact physician immediately.

SHIPPING AND STORAGE

Chem Pro 3810 is supplied in 5 gallon pails, and 30 gallon and 55 gallon drums. Store in safe, dry area away from heat or freezing.