



CHEM PRO LAB INC
WATER TREATMENT SPECIALISTS
CHEMICAL ENGINEERS
941 W 190TH ST, GARDENA, CA 90248
310-532-8611 - www.chemprolab.com

PRODUCT DATA SHEET

CHEM PRO 4500

PRINCIPAL USES

Chem Pro 4500 is used for removal of scale deposits in evaporative condensers, shell and tube condensers and steam boilers. It is inhibited to protect metal surfaces.

GENERAL DESCRIPTION

APPEARANCE:	Colorless to pale yellow.
ODOR:	Pungent, irritating odor
PRODUCT pH:	<1
DENSITY (lbs/gal):	10.1
FLASH POINT:	Not Flammable

DOSAGE

Proper Chem Pro 4500 treatment levels depend on many factors specific to a given system. The product should be used in accordance with Chem Pro Laboratory, Inc. recommendations and procedures for a particular system.

FEEDING

For scaled systems, use at 10% by volume levels in most applications. The pH should be at approximately 3. Carefully add to water systems. Consult Chem Pro for specific recommendations.

HANDLING

Read Safety Data Sheets before using.
Do not inhale or contact. Dangerous fumes and liquid. Contains inhibited muriatic acid. Wear eye and clothing protection. If contacted, wash with plenty of water for at least 15 minutes.
Keep containers closed when not in use.

SHIPPING AND STORAGE

Chem Pro 4500 is supplied in 5 gallon pails, and 30 gallon and 55 gallon drums.
Store in safe, dry area away from heat or freezing.